

Pro Tools

D400

D400[™] D400[₽]

Pro Tools

This guide shows you how to set up the D400 in Pro Tools. All pictures provided were taken with Pro Tools 12 but it is also applicable to most other Pro Tools versions.

All files mentioned in this guide can be found on the USB drive, in the Asparion Configurator installation folder or on our website.

If you are having trouble with anything in this guide, please contact us via our website <u>www.asparion.de/contact</u> and we'll immediately help you.

Step 1:

- Select the Pro Tools preset How to select a preset is described in the main manual.

Attention! Given that the resolution of a LED ring in the HUI protocol is only 11 it might seem like the LED ring jumps.

Attention! Given that the HUI protocol has no dedicated master volume, EQ and pan control the encoders might not have the desired function.

Step 2:

- Open Pro Tools
- Click on Setup->Peripherals...



2

en

Step 3:

- Go to Midi Controllers
- Choose HUI, D400, D400, 8

Peripherals EX									×
Synchronization	Machine Control	MIDI Control	llers	Ethernet C	ontrollers	Mic	Preamps	Satellites	VENUE
		Туре	Rec	eive From	Send To	D	# Ch's		
	#1	HUI	D 400	*	D 400	T	8 *		
	#2	none 💌	none	Ŧ	none	T			
	#3	none 💌	none	T	none	T			
	#4	none 🔻	none	~	none	Ŧ	T		
								Cancel	ОК

en

Step 4:

- In the factory preset these are the corresponding keys:

D400	Mackie				
1-8	F1-F8				
Shift	Shift				
Metronome	Сору				
Loop	Loop				
assignable 1	Undo				
assignable 2	Save				
*	Mixer				

4

en

Step 5: (optional)

- If you want to connect more than one extension, you should redo step 3 but select **D400 (2)**

If there is only one D400 showing up, you need to enable the extensions first. How you can do that is described in the main manual.



er



